



SAFETY DATA SHEET

1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation:

Name: REGATTA Yacht Varnish.

Product code: 34000

Company/undertaking identification:

Registered company name: DYRUP SAS.

Address: 101, avenue de la Châtaigneraie.92506.Rueil-Malmaison.France.

Telephone: 01 56 84 03 00. Fax:01 56 84 03 83. Telex:.

productsafety@dyrup.fr

www.dyrup.fr

Téléphone INRS / ORFILA: 01 45 42 59 59

Emergency telephone: + 33 (0)6 03 58 81 61.

Association/Organisation: INRS / ORFILA - http://www.centres-antipoison.net .

Use of the substance/preparation:

N/A

2 - HAZARDS IDENTIFICATION

This product is classed: Flammable.

May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

3 - COMPOSITION/INFORMATION ON INGREDIENTS

Full text of risk phrases appearing in section 3: see section 16.

Hazardous substances present on their own:

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

This preparation contains no hazardous substance in this category.

Other substances representing a hazard:

64742_48_9 CAS 64742-48-9 CE 265-150-3 NAPHTE LOURD (PETROLE), HYDROTRAITE | Concentration >=25.00% and <50.00%. Symbol: Xn R: 10-65-66

Substances present at a concentration below the minimum danger threshold:

INDEX 601-022-00-9 CAS 1330-20-7 CE 215-535-7 XYLENE | Concentration >=0.00% and <2.50%. Symbol: Xn R: 10-38-20/21

Other substances with occupational exposure limits:

No known substance in this category present.

Other components:

 64742_82_1 CAS 64742-82-1 CE 265-185-4 NAPHTE LOURD (PETROLE), HYDRODESULFURE | Concentration >=0.00% and <2.50%. Symbol: Xn N R: 10-65-66-67-51/53

INDEX 649-327-00-6 CAS 64742-48-9 CE 265-150-3 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY | Concentration >=0.00% and <2.50%. Symbol: Xn R: 65

May produce an allergic reaction:

INDEX 616-014-00-0 CAS 96-29-7 CE 202-496-6 2-BUTANONE OXIME | Concentration >=0.00% and <2.50%. Symbol: Xn R: 40.C3-41-43-21

 $68409_81_4 \quad CAS \; 68409-81-4 \quad CE \; 270-066-5 \qquad \text{ACIDES GRAS RAMIFIES EN C6-19, SELS DE COBALT (2+)} \; | \; \\ Concentration >= 0.00\% \; and \; < 2.50\%. \; Symbol: \; Xn \; N \; R: \; 38-43-51/53-22$

4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

In the event of exposure by inhalation:

If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.





In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

DO NOT use solvents or thinners.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

Suitable extinguishing media:

Carbon dioxide, chemical powders, foams, and other extinguishing gases.

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Extinguishing media which must not be used for safety reasons:

Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Special protective equipment for fire-fighters:

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions:

On account of the organic solvents contained in the preparation, eliminate sources of ignition and ventilate the premises. Avoid inhaling the vapors.

Consult the safety measures listed under headings 7 and 8.

Environmental precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Methods for cleaning up:

Clean preferably with a detergent, do not use solvents.

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Handling:

Handle in well-ventilated areas.

The vapors are denser than air. They can spread along the ground and form explosive mixtures with air

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Fire prevention:

Prevent the accumulation of electrostatic charges with connections to earth

The preparation may become electrostatically charged; always place on the ground during transfer. Wear antistatic shoes and clothes and make floors of conductive materials.

Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.





Recommended equipment and procedures:

For personal safety, see §8.

Observe precautions stated on label and also industrial safety regulations

Packages which have been opened must be reclosed carefully and stored in an upright position

Avoid inhaling vapors.

Prohibited equipment and procedures:

Smoking, eating and drinking are prohibited in premises where the preparation is used

Never open the packages under pressure

Storage:

Keep the container tightly closed in a dry place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Use personal protection equipment as per Directive 89/686/EEC.

Technical measures:

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.

If this ventilation is insufficient to maintain the concentration of solvent vapors below the exposure limits, wear breathing apparatus

Exposure limit values per INRS ED 984:

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N°:
1330-20-7	50	221	100	442	*	4 bis. 84 -

Exposure limit values per 2006/15/CE, 2000/39/EC and 98/24/EC:

EC	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:
1330-20-7	50	221	100	442	Peau

Exposure limit values (2003-2006):

Germany/AGW	AGW:	AGW:	Faktor:	Bemerkungen:	
1330-20-7	100 ml/m3	440 mg/m3	2(II)	DFG, H	
UK/WELs	TWA:	STEL:	Ceiling:	Definition:	Criterion:
1330-20-7	50 ppm	100 ppm	-	-	-
UK/OES	TWA:	STEL:	Ceiling:	Definition:	Criterion:
1330-20-7	50 ppm	100 ppm	-	-	-
ACGIH/TLV	TWA:	STEL:	Ceiling:	Definition:	Criterion:
1330-20-7	100 ppm	150 ppm	-	-	-

Respiratory protection:

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks. N/A

Hand protection:

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

In the event of prolonged or repeated contact with the hands, use appropriate gloves.

N/A

Eye and face protection:

Use eye protectors designed to protect against liquid splashes

N/A

Skin protection:

For further information, see § 11 of S.D.S. - Toxicological information.

N/A

9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:

Physical state: viscous liquid

Important health, safety and environmental information:





pH of the substance or preparation:

The pH is impossible to measure or its value is not relevant.

Boiling point/boiling range:

Flash point interval: vapour pressure:

Density: water solubility:

not specified.

not relevant.

23°C. < Flash point: <= 55°C. Below 110 kPa (1.10 bar).

< 1 Insoluble.

Other information:

melting point/melting range: not specified.

Self-ignition temperature: not specified.

Decomposition point/decomposition range: not specified.

10 - STABILITY AND REACTIVITY

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide

11 - TOXICOLOGICAL INFORMATION

No data is available regarding the preparation itself.

Exposure to vapors from solvents contained in the preparation beyond the exposure limits stated may produce effects harmful to health, such as:

Irritation of mucous membrane and respiratory system, kidneys, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic dermatitis on contact and absorption through the epidermis.

Splashes in the eyes may cause irritation and reversible damage

Other data:

CAS 1330-20-7: IARC Groupe 3 (The agent is not classifiable as to its carcinogenicity in to humans

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

13 - DISPOSAL CONSIDERATIONS

Do not pour into drains or waterways.

Waste

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

14 - TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2007 - IMDG 2006 - ICAO/IATA 2007).

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

ADR/RID	Class	Code	Pack gr.	Label	ldent.	LQ	Provis.	
	3	F1	III	3	30	LQ7	163 640 65	0E
	Not subject	to this regula	ation if Q < 45	50I.				
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.		
	3	-	III	5 L	F-E,S-E	163 223 94	4 955	
	Not subject	to this regula	ation if Q < 30	Ol				
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note
	3	-	III	309	60 L	310	220 L	A3 A72
	3	-	Ш	Y309	10 L	-	-	-

15 - REGULATORY INFORMATION

This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations





In addition directive 2004/73/EC with the 29° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

Preparation classification:

Flammable.

Contains:

Contains 616-014-00-0 2-BUTANONE OXIME. May produce an allergic reaction.

Contains 68409_81_4 ACIDES GRAS RAMIFIES EN C6-19, SELS DE COBALT (2+). May produce an allergic reaction.

Particular hazards associated with the preparation and safety recommendations:

R 10	Flammable.
R 66	Repeated exposure may cause skin dryness or cracking.
S 2	Keep out of the reach of children.
S 46	If swallowed, seek medical advice immediately and show this container or label.
S 23	Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
S 24	Avoid contact with skin.
S 51	Use only in well-ventilated areas.
S 62 label	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or

16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

Full text of risk phrases appearing in section 2:

	3
R 10	Flammable.
R 20/21	Harmful by inhalation and in contact with skin.
R 21	Harmful in contact with skin.
R 22	Harmful if swallowed.
R 38	Irritating to skin.
R 40.C3	Limited evidence of a carcinogenic effect.
R 41	Risk of serious damage to eyes.
R 43	May cause sensitisation by skin contact.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 65	Harmful: may cause lung damage if swallowed.
R 66	Repeated exposure may cause skin dryness or cracking.
R 67	Vapours may cause drowsiness and dizziness.

2004/42/EC (COV):

The permitted European level of VOC in the ready-to-use product (category IIAe) is 500 g/l maximum (2007).

The permitted European level of VOC in this ready-to-use product is limited to 499 g/l.

09/06/2009